

AQUAHEALTH® PREMIUM WATER

Bottled water quality in every glass™

QUICKFILL 540 DISPENSER



INSTALLATION REQUIREMENTS

SPACE ALLOTMENT

BASE: 10-3/8 inches wide x 25-1/4 inches deep
HEIGHT: 24 inches (without legs) 28 inches (with legs)

SHIPPING WEIGHT	108 LBS
OPERATING WEIGHT	125 LBS
REFRIGERATION MOTOR	1/4 HP

ELECTRICAL REQUIREMENTS

Use a separate 115 VAC, 60HZ, 1PH, 15 AMP grounded duplex outlet to accommodate each dispenser and accessory. Locate the outlet within 5 feet of the dispenser. Extension cords cannot be used.

ALL ELECTRICAL WIRING MUST CONFORM TO NATIONAL AND LOCAL ELECTRICAL CODES.

Running amps: 7

INSTALLATION CONSIDERATIONS

The countertop must be capable of holding the weight of the unit and also have enough clearance above to accommodate its height. It is necessary to drill a 2-1/2 inch hole in the counter top to accommodate the drain and product lines equivalent space to run the lines behind the cabinet.

PLUMBING REQUIREMENTS

It is necessary to supply the Quickfill 540 with AquaHealth Premium Water. Syrup flavors are optional. Syrup supply lines are braided and have a 1/4-inch inside diameter. Reducing union are required to reduce from 3/8 to 1/4 inch barb for all syrup connections. The Non-Sparkling Water and optional carbonated water supply lines are braided and have a 3/8-inch inside diameter. The Quickfill 540 maintains a drain provision that can be plumbed or the tray can be removed as required for manual operation.



AQUAHEALTH®
Incorporated

475 Washington Street, Wrentham, Massachusetts 02093

E-mail: info@aquaealth.com

Web Site: www.aquaealth.com

1-800-795-4975